



Directions: Clean floor and apply two thin coats of floor finish with a dedicated rayon mop. Wait one hour between coats. Consult application procedure for details and precise instructions.

Maintenance: Sweep or damp mop daily to remove dirt. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use the 4100 Restorer Cleaner. Consult maintenance procedure for details and precise instructions.

Product #40001; 4 gallons per case Product #40005; 5-gallon pail Product #40002; 54-gallon drum



Low Cost + High Performance = Value

Staticide® Acrylic Floor Finish offers high-tech static protection at a reasonable price. This economical formula leaves a durable, glossy finish that can last up to twelve months, making it a popular choice for budget-minded companies with industrial areas where static control is essential.

Easy to apply and maintain, Staticide® Acrylic Floor Finish leaves floors with a surface resistivity of 108 -109 ohms per square, complying with ANSI/ESD S20.20 guidelines. This water-based formula is UL listed for slip resistance, RoHS compliant, biodegradable, non-flammable, and free of formaldehyde, phthalates, alkalis, acids, and ammonia.

As ACL's original ESD floor finish, Staticide® Acrylic continues to be an ideal choice for production areas, warehousing, shipping, laboratories, and electronic repair facilities.

- Ooverage: 1,500 2,000 square feet per gallon
- **Results** Non-toxic; biodegradable
- Non-volatile solids: 20 ± 5%
- **Strip cycle: 6-12 months**
- Buitable to use on vinyl, linoleum, and ceramic tiles
- Surface resistivity: 10⁸ 10⁹ ohms per square (average)
- **&** Low V.O.C.
- **Water-based polyurethane**





ACL Staticide

840 W.49th Place · Chicago, IL 60609 800.782.8420 · 847.981.9212 · fax 847.981.9278 info@aclstaticide.com · www.aclstaticide.com

