

ULTRA TAPE™

PARTICLE-FREE TAPE FOR CRITICAL ENVIRONMENTS

Cleanroom Anti-Static Cellophane Tape ULTRATAPE #2127 & #0127 (Formerly X131)



This transparent cellophane tape is naturally anti-static. Has a high tack rubber adhesive, which typically leaves no residues. Great for general sealing and packaging in cleanroom or semi-cleanroom ESD areas. The workhorse of the ESD industry. 100 volts max upon removal from most surfaces.

Cellophane tape *printed* with ESD emblems is also available as our products #2137/#0137.

PROPERTIES OF TAPE:

Substrate:	Cellophane	Operating Temp:	32-150 °F (0 to 66°C)
Adhesive:	Rubber	Elongation at Break:	20%
Total Thickness:	2.0 Mil	Tensile Strength:	25 lbs/inch width
Adhesion to Steel:	34 oz./inch width	Length:	72 yds
		Core:	3"OD Plastic Core

Color: Clear (Transparent Brown)



CLEANING & BAGGING

Following our clean manufacturing process, each roll is individually inspected and individually wrapped in clean polyethylene bags; one to twelve of these (depending on tape width) go into each secondary bag.

PRODUCT PACKAGING AND CLEANLINESS: OPTIONS		
#2127	Class 100	Double bagged; each roll is individually bagged. One to six of these (depending on tape width) goes into each sealed secondary bag.
# 0127	Class 1,000+	Individual rolls are in unsealed bag. Plastic core. Each box contains an unsealed box bag.

Notice: Each user should conduct his own tests and analysis to determine the product's suitability for his intended use and shall assume all responsibility and liability. Information above is solely intended as guidelines for conducting such tests. Ultratape™ Industries liability is limited to replacing defective product. TSA-050

Visit us at www.cleanroomtape.com

Ultratape Industries, Inc – 2814 19th St. SE - Salem OR 97302 - 503-540-8946 - Fax: 503-365-8005 –
ultratape@cleanroomtape.com