

TECHNICAL SPECIFICATION

Model spec: DRY540 Series

Description: auto dry cabinet of 540 litre storage capacity for humidity control, 2 windows and 3 shelves.

Storage capacity: 540 Litres

Shelf Quantity: 3 (removable and adjustable for up/down.)

Outer dimensions: W598*D710*H1465mm

Inner dimensions: W596*D682*H1298mm

Technical features:

- 1.6 LED display panels, **Honeywell** humidity sensor with error of $\pm 3\%RH$;
- 2.High grade 1mm and 1.2mm cold rolled plate, reinforced structure design,high intensity bearing, every shelf can bear over 150kg;
- 3.3.2mm toughened glass.
- 4.**Zinc alloy lock** with air tightness;
- 5.ROHS certified surface painting with **Dupont** powder;
- 6.Power supply: AC power 85V~265V 50/60Hz;
7. ESD safe high intensity truckles of which two in front are brakable;
8. Cool looking of Dark green surface (anti-ESD) or White (non-ESD protection) for customer's options.
9. Designed as per IPC/JEDEC J-STD-033B; CE certified.
10. Options for customer's special demands:
 - 1) data logging system by USD connection with computer for data reading and printing;
 - 2) security code lock;
 - 3) alarm system with light tower;
 - 4) heating system up to **40C**, for low temperature baking;
 - 5) high flow air injection system for up to 300LPM.
 - 6) independent segregated compartments.
 - 7) stainless steel cabinet.

Package size: W60*D80*H165CM

Gross weight: 100KG

Net weight: 70KG

Specifications chart:

SPEC	Controlled Humidity (RH)	Average Power (W)	Maximum Power (W)	Anti-ESD Function (Y/N)
DRY540A	20%~60%	20	140	N
DRY540B	10%~20%	40	280	N
DRY540C	1%~10%	60	420	N
DRY540U	1%~5%	60	420	N
DRY540EA	20%~60%	20	140	Y
DRY540EB	10%~20%	40	280	Y
DRY540EC	1%~10%	60	420	Y
DRY540EU	1%~5%	60	420	Y

Sample Photos:

