

Dry870 Series

Outer dimension:W900*D600*H1890 mm
 Inner dimension:W898*D572*H1698 mm



Dry1436 Series

Outer dimension:W1200*D710*H1910 mm
 Inner dimension:W1198*D682*H1723 mm



SPEC	Controlled Humidity (RH)	Average Power (W)	Maximum Power (W)	Anti-ESD Function (Y/N)
DRY870A	20%~60%	40	280	N
DRY870B	10%~20%	40	280	N
DRY870C	1%~10%	80	560	N
DRY870U	1%~5%	80	560	N
DRY870EA	20%~60%	40	280	Y
DRY870EB	10%~20%	40	280	Y
DRY870EC	1%~10%	80	560	Y
DRY870EU	1%~5%	80	560	Y

SPEC	Controlled Humidity (RH)	Average Power (W)	Maximum Power (W)	Anti-ESD Function (Y/N)
DRY1436A-4/DRY1436A-6	20%~60%	40	280	N
DRY1436B-4/DRY1436B-6	10%~20%	80	560	N
DRY1436C-4/DRY1436C-6	1%~10%	120	840	N
DRY1436U-4/DRY1436U-6	1%~5%	120	840	N
DRY1436EA-4/DRY1436EA-6	20%~60%	40	280	Y
DRY1436EB-4/DRY1436EB-6	10%~20%	80	560	Y
DRY1436EC-4/DRY1436EC-6	1%~10%	120	840	Y
DRY1436EU-4/DRY1436EU-6	1%~5%	120	840	Y