



WY-200 Dual Workstation Monitor



*To Monitor
Personnel and
ESD Mat Grounding*

WY-200 is a multi-feature continuous monitor. It is a dual workstation ESD monitor designed specifically for price-sensitive users. The personnel capacitance to earth is used during monitoring. The unit is made with reliable SMT technology with solid housing. It is able to simultaneously monitor the ESD grounding of 2 traditional single-wire wrist-straps and 2 ESD table mats.

Key Features:

- Simultaneously monitor 2 traditional wrist-straps and 2 ESD table mats.
- LED and audio indicators for wrist-strap and ESD mat grounding status.
- Stand-by indicator: Power is on but wrist-strap is not plugged in.
- Alarm audio sound volume is adjustable.
- Operator sensitivity is adjustable.
- ESD mat resistance limit: $100M\Omega \pm 10\%$
- Wrist-strap alarms can be connected to external industrial grade siren.
- Dimension (W×H×L): 4×1×3 inch (10×2.5×7.5 cm)
- Typical capacitor tests: pass 122pF, fail 75pF



(Ver. 2015.06)

MEGALIN Source International Megalin Source International Co., Ltd.

• www.megalinsource.com • E-mail: sales@megalinsource.com
• Address: 3F-6 No.81 Sec.1 Xintai 5th Road, Xizhi District, New Taipei City 22101, Taiwan • TEL: +886-2- 8698-4181 (Main)
• China Shenzhen/ Suzhou TEL: +86-755-2774-6923

(© Megalin Source All Rights Reserved)