

ULTRA TAPE™

PARTICLE-FREE TAPE FOR CRITICAL ENVIRONMENTS

Cleanroom Hazard Warning (& Floor Marking) Tape **ULTRATAPE #1165**

Floor Marking/Hazard Warning tapes in a variety of colors. Adheres well to all surfaces. The #1165 has a durable finish for floor marking, and will last for months or years, depending on traffic and conditions. Length = 18 yards (16.5 M). Normal widths are 2" (5 cm) and 3" (7.6 cm). Custom widths available.

PROPERTIES OF TAPE:

<p>Substrate: Overlaminated PVC Adhesive: Rubber Total Thickness: 9.0 Mil Adhesion to Steel: 17 oz./inch width</p>	<p>Elongation at Break: 120% Tensile Strength: 20 lbs./inch width Length: 18 Yards</p>
---	---

OSHA DESIGNATION	
Red/White:	Fire Alarms & Equipment
Green/White:	Safety Equipment & Location
Black/Yellow:	Caution Areas



PRODUCT PACKAGING AND CLEANLINESS: OPTIONS		
#1165	Class 100	<i>Double bagged; each roll is individually bagged. One to six of these (depending on tape width) goes into each sealed secondary bag.</i>
# 0165	Class 10,000+	<i>Individual rolls are in unsealed bag. Plastic core. Each box contains an unsealed box bag.</i>

CLEANING & BAGGING

Following our clean manufacturing process, each roll is individually inspected and individually wrapped in clean polyethylene bags; one to six of these (depending on tape width) go into each secondary bag. Statistical process control assures product particulate levels to be below 5/roll.

Notice: Each user should conduct his own tests and analysis to determine the product's suitability for his intended use and shall assume all responsibility and liability. Information above is solely intended as guidelines for conducting such tests. Ultratape™ Industries liability is limited to replacing defective product. SA-99-036

Visit us at www.cleanroomtape.com

Ultratape Industries, Inc – 2814 19th St. SE - Salem OR 97302 - 503-540-8946 - Fax: 503-365-8005 – ultratape@cleanroomtape.com